

# Specialty Venetian Blinds Specification - Aluminium

### System

Horiso Specialty Venetian Blinds - N80 / N100 / N150

## Operation

#### External or Internal Installation

- Manual control by crank or pull cord (pull cord is for internal installation only. Available in White)
- Motorised control via switch, remote control or tablet/hand-held device.
- Automation control at varying degrees of customisation.



## **System Limitations**

# Asynchronous box motors

- Quiet and reliable lift/tilt motor with soft break. 110 or 240 volts
- UL certified motors
- Compatibility with home automation systems and building management systems
- Adjustable end limits

## Slats

Slat Material: Coating:

Slat Widths:

Crowned AA 5050 marine grade aluminium with chromate conversion undercoat. High UV resistant (RUV3) PE (polyester) coil coating.

Colours:



Custom colours, perforated slats and timber slats available on request.

80 mm / 100mm / 150mm Slat Profile: 80 mm 100mm 150mm





Solid Slat

Perforated Slat

### Components

Aluminium components: 25 micron clear anodized

Heavy duty cables: Stainless steel cable with stainless

steel mushroom head

Lifting and tilting device: High-strength, shrink-resistant and

reinforced 100% Kevlar

**Termination Brackets:** L shapes face fix bracket

> Bottom termination (M8 Swage) Top hat bottom termination bracket

All steel components are stainless steel 316 marine grade



Internal or external installation.

- Installation into existing building recesses.
- Installation using top fix pelmet fitted onto building structure. Pelmet extensions are available.
- Installation using face fix pelmet fitted onto building structure. Pelmet extensions are available.
- Recommended use of a wind sensor for external installation for automatic retraction in high winds.

## **System Limitations**

Maximum coverage per system: 45 sqm.

Maximum width: 6m.


Maximum drop: 7m / 9m (XL).


A centre cable is required for widths over 3m for external installations and extreme high wind areas.

# Pelmets / Fascias


Top fix W: 145mm/ H: 150mm







Face fix W: 154mm/ H: 150mm Wall bracket: 18mm



Pelmet extension 50mm increments



- Extruded aluminium 3 mm.
- Powder-coated in standard or custom colours, 25 micron clear anodised.
- Pelmet/fascia extensions in 50 mm increments.
- Custom pelmet/fascia solutions

For stacking height information, please refer to the Specialty Venetian Blind brochure

