



## System

Horiso® Specialty Venetian Blinds - Timber

## Operation

### Internal or External Installation

- Manual control by crank or pull cord. Pull cord is for internal installation only. Available only in a standard combination colour of white & black.
- Motorised control via switch, remote control or tablet/hand-held device.
- Automation control possible via third parties.



## Motor


Asynchronous box motors

- Quiet and reliable lift/tilt motor with soft break. 110 or 240 volts.
- UL certified motors.
- Compatibility with home automation systems and building management systems.
- Adjustable end limits.

## Timber Slats

### Western red cedar

**Use:** Internal / External

**Slat Widths:** Standard 84mm wide x 4mm 

**Colour Options:** All oil finishes have either a clear, single or double coating (as shown below)



## Components

- Aluminium components:** 25 micron clear anodised.
- Heavy duty cables:** Stainless steel cable with stainless steel mushroom head.
- Lifting and tilting device:** High-strength, shrink-resistant and reinforced 100% Kevlar.
- Termination Brackets:** L shaped face fix bracket.  
M8 concrete drop in anchor for bottom fix termination.  
S/S timber rampa screw for bottom fix termination  
Top hat bottom termination bracket
- All steel components are stainless steel 316 marine grade.

## Installation

Internal or external installation.

- Installation into existing building recesses.
- Installation using top fix pelmet fitted onto building structure. Pelmet extensions are available.
- Installation using face fix pelmet fitted onto building structure. Pelmet extensions are available.
- Recommended use of a wind sensor for external installation for automatic retraction in high winds.

## System Limitations


Maximum coverage

- 3.3m width x 4m drop per system. For larger sizes, please contact Horiso®.
- A centre cable is required for widths of over 3m on external installations and extreme high wind areas.


## Pelmets (Fascias)

### Top fix

W: 145mm / H: 150mm




### Top fix with end plate




### Face fix

W: 154mm / H: 150mm  
Wall bracket: 18mm



### Pelmet extension 50mm increments



- Extruded aluminium 3mm.
- 25 micron clear anodised or powder coated in standard or custom colours.
- Pelmet/fascia extensions in 50 mm increments.
- Custom pelmet solutions available.

For stacking height information, please contact Horiso®

